

the
safer
tank™



ZCL tanks...

Well Worth it!™

Safe, long lasting secondary containment oilfield tanks

ZCL
EVERLAST SYSTEMS



Well Worth it!™

*The long-lasting
'tank-within-a tank'
lining system that simply
will not corrode!*

Corrosion-resistant Fiberglass Liner

The Everlast Secondary Containment Tank is a steel structure with an internal fiberglass 'tank-within-a-tank' that simply will not corrode. A durable fiberglass reinforced plastic (FRP) liner is applied to the inside steel plate surface. The result is a 'best of both worlds' design that extends tank life and makes monitoring fast & easy, eliminating the problem of undetected leakage.

The G55 Compliant Oilfield Solution

G55 compliant, Everlast tanks are recognized as a secondary containment system by both the Alberta Energy & Utilities Board (AEUB) and Alberta Environmental Protection (AEP). ZCL double wall tanks fulfill all the requirements of safe secondary containment of produced water, brine, condensate, and crude.

A Complete 'Turn-Key' Package

Operational ready, the Everlast system is a skid mounted storage package complete with an explosion-proof catadyne heating system. Reusable, tanks can be moved for installation at a new location, even after many years of trouble-free service.

Features

- Guide 55 recognized secondary containment system
- Holding capacities of 50, 100, 200 & 400 BBL
- Enclosed inlet & outlet (doghouse) piping assembly
- Explosion-proof catadyne heating system
- Structural Plate: ASTM A36 or Equal
- FRP liner with monitorable interstitial space
- Integral 1-to-1 mechanical EZ-Read level gauge
- Urethane foam insulation with UV inhibitor coating



Fabric panels are saturated with resin, curing to create an interstitial space.



Additional features include integral lift lugs, mechanical liquid level gauge, thief hatch, battery cables, ground wire and ladder.

Standard Models

	Diameter		Height		Weight	
	ft	m	ft	m	lbs.	kg
50 BBL d/w	7'9"	2.36	6'	1.83	2,800	1270
100 BBL d/w	9'6"	2.90	8'	2.44	4,800	2180
200 BBL d/w	12'	3.66	10'	3.05	7,600	3450
400 BBL d/w	12'	3.66	20'	6.10	12,000	5440

ZCL
EVERLAST SYSTEMS

1-800-661-8265
www.zcl.com

