

No Dikes or
Liners Required!

New!

Simply will not corrode!

ZCL Direct Burial 50psi Flare
Knock Out or Drain Double Wall
Pressure Vessel

Relaxed backfill
specifications for ZCL's
double wall fiberglass vessels

Introducing relaxed backfill specifications for ZCL's double wall fiberglass vessels

Filament wound 50PSI (non code) designed fiberglass underground pressure vessels for the safe containment of produced water and liquids from flare gas streams.

Extremely durable (yet cost effective), these Drain and FKO pressure vessels are designed for **quick and easy installation**.

They can be buried almost anywhere, **using virtually any backfill material available** including sand, gravel, selected native backfill, granular soil.

Double wall fiberglass construction (choose from 50 or 99 Barrel) **allows you to comply with current G-55 guidelines** for safe containment, while greatly reducing your risk of expensive leak-related cleanups over the long haul.

- 50psi Filament wound fiberglass primary storage & 100% secondary containment
- Moveable (1/2 the weight of other tanks) and reusable
- Operation-ready– quick, easy and inexpensive installation
- Corrosion resistant to produced water & most chemicals
- Minimal site preparation required
- Choice of 50BBL or 99BBL

Meets G-55 regulatory guidelines for safe containment



Satisfaction
100%
Guaranteed

The corrosion free advantage...

Corrosion Free...100% premium grade double wall Fiberglass Reinforced Plastic (FRP) construction (no filler) provides corrosion free internal and external service.

ZCL tanks are suitable for 15% Hydrogen Sulfide content at 170° F.



Canada's #1 fiberglass tank manufacturer.

ZCL
COMPOSITES INC.



Visit Our Web Site: www.zcl.com
Call Us Today 1-800-661-8265